

Description


Silicon Carbide (SiC) MOSFET use a completely new technology that provide superior switching performance and higher reliability compared to Silicon. In addition, the low ON resistance and compact chip size ensure low capacitance and gate charge. Consequently, system benefits include highest efficiency, faster operating frequency, increased power density, reduced EMI, and reduced system size.

Features

- High Speed Switching with Low Capacitances
- High Blocking Voltage with Low RDS(on)
- Optimized package with separate driver source pin
- Easy to parallel and simple to drive
- ROHS Compliant, Halogen free

Application

- EV Charging
- DC/DC Converters
- Switch Mode Power Supplies
- Power Factor Correction Modules
- Solar PV inverters


Ordering Information

Part Number	Marking	Package	Packaging
JX4S0060R065M	JX4S0060R065M	TO-247	Tube

Absolute Maximum Ratings(Tc=25°C)

Symbol	Parameter	Value	Unit
V _{DS}	Drain-Source Voltage	650	V
I _D	Drain Current(continuous)at Tc=25°C	36	A
I _D	Drain Current(continuous)at Tc=100°C	26	A
I _{DM}	Drain Current (pulsed)	100	A
V _{GS}	Gate-Source Voltage	-10/+22	V
P _D	Power Dissipation Tc = 25°C	150	W
T _J , T _{stg}	Junction and Storage Temperature Range	-55 to +150	°C

Electrical Characteristics(T_J = 25°C unless otherwise specified)
Typical Performance-Static

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
BV _{DS}	Drain-source Breakdown Voltage	I _D =250uA, V _{GS} =0V	650			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =650V, V _{GS} =0V, T _J =25°C			100	μA
I _{GSS}	Gate-body Leakage Current	V _{DS} =0 V ; V _{GS} =-10 to 20V		10	250	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D =5mA	2	3	4	V
V _{GSon}	Recommended turn-on Voltage	Static		20		V
V _{GSoff}	Recommended turn-off Voltage			-5		V
R _{DS(on)}	Static Drain-source On Resistance	V _{GS} =20V, I _D =15A		60	80	mΩ
		V _{GS} =20V, I _D =15A T _J =150°C		75		mΩ

Typical Performance-Dynamic

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
C _{iss}	Input Capacitance	V _{DS} =600V, f=1MHz, V _{AC} =25mV		1138		pF
C _{oss}	Output Capacitance			88.8		pF
C _{rss}	Reverse Transfer Capacitance			9.6		pF
g _{fs}	Transconductance	V _{DS} =20V, I _D =15A		11		S
E _{oss}	Coss Stored Energy	V _{DS} =600V, f=1MHz		17		μJ
E _{on}	Turn-On Energy (Body Diode)	V _{DS} =400V, V _{GS} =-5/20V, I _D =15A, L=150μH T _J =150°C		75		μJ
E _{off}	Turn-Off Energy (Body Diode)			8.6		μJ
Q _g	Total Gate Charge	V _{DS} =400V, V _{GS} =-5V/20V, I _D =15A		64		nC
Q _{gs}	Gate-source Charge			13.5		nC
Q _{gd}	Gate-Drain Charge			18.3		nC
R _{G(int)}	Internal Gate Resistance	f=1MHz, V _{AC} =25mV		3		Ω
t _{d(on)}	Turn-on Delay Time	V _{DS} =400V, V _{GS} =-5V/20V, I _D =15A, L=150 μH R _{ext} =2.5Ω		10		ns
t _r	Rise Time			13.8		ns
t _{d(off)}	Turn-off Delay Time			20		ns
t _f	Fall Time			8.8		ns

Typical Performance-Reverse Diode(T_J = 25°C unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{FSD}	Forward Voltage	V _{GS} =0V, I _F =7.5A, T _J =25°C		5.2	6	V
		V _{GS} =0V, I _F =7.5A, T _J =150°C		4.8	6	V
I _S	Continuous Diode Forward Current	V _{GS} =0V, T _C =25°C		22		A
t _{rr}	Reverse Recovery Time	V _{GS} =-5V, I _F =15A, V _R =400V, T _J =150°C di/dt=2400A/μs		19		nS
Q _{rr}	Reverse Recovery Charge			120		nC
I _{rrm}	Peak Reverse Recovery Current			15		A

Thermal Characteristics

Symbol	Parameter	Value.	Unit
R _{θJC}	Thermal Resistance, Junction-to-Case	0.83	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient	40	°C/W

The values are based on the junction-to case thermal impedance which is measured with the device mounted to a large heat sink assuming maximum junction temperature of T_{J(max)}=150°C

Electrical Characteristics

Fig1. Output characteristics ($T_J = 25^\circ\text{C}$)




Fig2. Output characteristics ($T_J = 150^\circ\text{C}$)




Fig3. Normalized On-Resistance vs. Temperature




Fig4. On-Resistance vs. Temperature




Fig5. Transfer Characteristic




Fig6. Body Diode Characteristic at 25°C




Fig7. Threshold Voltage vs. Temperature




Fig8. Gate Charge Characteristics




Fig9. 3rd Quadrant Characteristic at 25°C




Fig10. Output Capacitor Stored Energy




Fig11. Capacitances vs. Drain-Source




Fig12. Max Power Dissipation Derating Vs Tc




Fig13. Switching Energy vs. Drain Current




Fig14. Switching Energy vs. RG(ext)




Fig15. Switching Energy vs. Temperature




Fig16. Switching Times vs. RG(ext)




Fig17. Transient Thermal Impedance






Fig18. Safe Operating Area



Package Drawing:

Dimensions (UNIT: mm)

SYMBDLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	4.9	5	5.1	0.193	0.197	0.201
A1	2.31	2.42	2.52	0.091	0.095	0.099
A2	1.9	2	2.1	0.075	0.079	0.083
b	1.16	1.22	1.27	0.046	0.048	0.050
b1	1.15	1.2	1.25	0.045	0.047	0.049
b2	2.61	2.76	2.91	0.103	0.109	0.115
b3	1.36	1.42	1.47	0.054	0.056	0.058
C	0.59	0.62	0.66	0.023	0.024	0.026
D	20.9	21	21.1	0.823	0.827	0.831
D1	15.94	16.24	16.54	0.628	0.639	0.651
D2		5		0.197 TYP		
D3	0.8	0.95	1.1	0.031	0.037	0.043
e	5.08 BSC			0.200 BSC		
e1	2.54 BSC			0.100BSC		
E	16.05	16.15	16.25	0.632	0.636	0.640
E1	13.82	14.02	14.26	0.544	0.552	0.561
L	19.75	19.95	20.15	0.778	0.785	0.793
L1	---	---	3.87	---	---	0.152
Q	5.95 BSC			0.234BSC		
ØP	3.45	3.6	3.75	0.136	0.142	0.148