



SEA & LAND ELECTRONIC CORP.

WWW.SEALAND-PPTC.COM

ALPHA-TOP TECHNOLOGY CORP.

WWW.ALPHA-TOP.CN

APPROVAL SHEET

MODEL NO.:	SMD Series
------------	------------

CUSTOMER:
CUSTOMER'S APPROVAL:
AUTHORIZED SIGNATURE/STAMP:
DATE

MANUFACTURER:
HEAD OFFICE:
13F.,No.120-10,Sec.3,Zhongshan Rd.,Zhonghe Dist.,New Taipei City 23544,Taiwan Tel: 886-2-8221-2567 Fax:882-2-2225-7268 E-mail:service@chipfast.com.tw
China Branch:
Factory Building B)Shuangpeng,Weibu Village, Qiuchang Town, Huiyang District, Huizhou City, Guangdong Province, P.R.C.) Tel: 86-752-3562001 Fax:86-752-3558696 E-mail:service@atpptc.com

Submitted by:	Chen
Approved by:	YC Lin
DATE:	24-Jun-22

SEA & LAND ELECTRONIC CORP.



- Features**
- Surface Mount Devices
 - Lead free device
 - Size 7.5*5.5 mm 0.29*0.20 inch
 - Surface Mount packaging for automated assembly

- Applications**
- Almost anywhere there is a low voltage power supply, up to 60V and a load to be protected, including:
- Computer mother board, Modem.
 - Telecommunication equipments.

SMD Series

Alpha-Top (Sea & Land Alliance)

Performance Specification

Model	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance		Agency Approval	
						Current (A)	Time (Sec)	R _{i min} (Ω)	R _{1 max} (Ω)	UL	TUV
SMD030L	60	100	0.30	0.60	1.5	1.5	3.0	0.600	4.800		
SMD050L	60	100	0.50	1.00	1.5	2.5	4.0	0.180	1.400		
SMD075L	33	100	0.75	1.50	1.5	8.0	0.3	0.100	1.000		
SMD075L-60V	60	100	0.75	1.50	1.5	8.0	0.3	0.100	1.000		
SMD100L	33	100	1.10	2.20	1.5	8.0	0.5	0.065	0.410		
SMD125L	33	100	1.25	2.50	1.5	8.0	2.0	0.050	0.250		
SMD150L	33	100	1.50	3.00	1.5	8.0	2.0	0.035	0.230	✓	
SMD185L	33	100	1.85	3.70	1.5	8.0	2.5	0.030	0.150	✓	
SMD200L	16	100	2.00	4.00	1.5	8.0	4.5	0.020	0.120		
SMD200L-24V	24	100	2.00	4.00	1.5	8.0	4.5	0.020	0.120		
SMD250L	16	100	2.50	5.00	1.5	8.0	16.0	0.020	0.085		
SMD260L	6	100	2.60	5.20	1.5	8.0	10.0	0.014	0.075		
SMD300L	6	100	3.00	6.00	1.5	8.0	20.0	0.012	0.048	✓	
SMD300L-13.2V	13.2	100	3.00	6.00	1.5	8.0	20.0	0.012	0.048	✓	
SMD300L-16V	16	100	3.00	6.00	1.5	8.0	20.0	0.012	0.048	✓	
SMD300L-24V	24	100	3.00	6.00	1.5	8.0	20.0	0.012	0.048		
SMD400L	6	40	4.00	8.00	1.5	16.0	20.0	0.012	0.035		
SMD400L-16V	16	40	4.00	8.00	1.8	16.0	20.0	0.012	0.035		
SMD400L-24V	24	40	4.00	8.00	1.8	16.0	20.0	0.012	0.035		
SMD500L	6	40	5.00	10.00	1.8	20.0	10.0	0.005	0.031		
SMD500L-13.2V	13.2	40	5.00	10.00	1.8	20.0	10.0	0.005	0.031		
SMD500L-24V	24	40	5.00	10.00	1.8	20.0	10.0	0.005	0.031		
SMD600L	6	40	6.00	12.00	1.8	25.0	8.0	0.004	0.026		
SMD600L-13.2V	13.2	40	6.00	12.00	1.8	25.0	8.0	0.004	0.026		
SMD600L-16V	16	40	6.00	12.00	1.8	25.0	8.0	0.004	0.026		
SMD600L-24V	24	40	6.00	12.00	1.8	25.0	8.0	0.004	0.026		
SMD700L	6	40	7.00	14.00	1.8	35.0	2.0	0.002	0.018		
SMD700L-13.2V	13.2	40	7.00	14.00	1.8	35.0	2.0	0.002	0.018		
SMD800L	6	40	8.00	16.00	1.8	35.0	2.5	0.001	0.010		

Ihold = Hold Current. Maximum current device will not trip in 25°C still air.
Itrip = Trip Current. Minimum current at which the device will always trip in 25°C still air.
Vmax = Maximum operating voltage device can withstand without damage at rated current (Imax).
Imax = Maximum fault current device can withstand without damage at rated voltage (Vmax).
Pd = Power dissipation when device is in the tripped state in 25°C still air environment at rated voltage.
Rimin/max = Minimum/Maximum device resistance prior to tripping at 25°C.
R1max = Maximum device resistance is measured one hour post reflow.
CAUTION : Operation beyond the specified ratings may result in damage and possible arcing and flame.

Environmental Specifications

Test	Conditions
Passive aging	+85°C, 1000 hrs.
Humidity aging	+85°C, 85% R.H. , 168 hours
Thermal shock	+85°C to -40°C, 20 times
Resistance to solvent	MIL-STD-202, Method 215
Vibration	MIL-STD-202, Method 201
Ambient operating conditions : - 40 °C to +85 °C	
Maximum surface temperature of the device in the tripped state is 125 °C	
In case of special use, please contact our engineer	

Agency Approvals :



E201504(Alpha-Top)/E319079(Sea&Land)

Regulation/Standard:



2015/863/EU



EN14582




I_{hold} Versus Temperature

Model	Maximum ambient operating temperature (T _{max}) vs. hold current (I _{hold})									
	-40°C	-20°C	0°C	25°C	40°C	50°C	60°C	70°C	85°C	
SMD030L	0.45	0.40	0.35	0.30	0.25	0.23	0.20	0.17	0.14	
SMD050L	0.76	0.67	0.59	0.50	0.42	0.38	0.33	0.29	0.23	
SMD075L	1.13	1.01	0.88	0.75	0.62	0.56	0.50	0.44	0.34	
SMD100L	1.66	1.47	1.29	1.10	0.91	0.83	0.73	0.64	0.50	
SMD125L	1.89	1.68	1.46	1.25	1.04	0.94	0.83	0.73	0.56	
SMD150L	2.27	2.01	1.76	1.50	1.25	1.13	1.00	0.87	0.74	
SMD185L	2.80	2.47	2.17	1.85	1.54	1.39	1.22	1.07	0.85	
SMD200L	3.02	2.68	2.34	2.00	1.66	1.50	1.32	1.16	0.90	
SMD250L	3.78	3.35	2.93	2.50	2.08	1.88	1.65	1.45	1.13	
SMD260L	3.64	3.25	2.91	2.60	2.26	2.08	1.95	1.74	1.13	
SMD300L	4.53	4.02	3.51	3.00	2.52	2.26	1.99	1.75	1.34	
SMD400L	5.97	5.30	4.66	4.00	3.36	3.04	2.71	2.38	1.83	
SMD500L	7.55	6.70	5.85	5.00	4.15	3.75	3.30	2.90	2.25	
SMD600L	8.60	7.75	6.89	6.00	5.04	4.56	3.96	3.54	2.76	
SMD700L	9.50	8.70	7.90	7.00	6.40	5.85	5.40	4.80	3.95	
SMD800L	10.80	9.76	8.80	8.00	6.56	6.08	5.44	4.80	3.68	

Construction And Dimension (Unit:mm)


Model	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SMD030L	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30
SMD050L	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30
SMD075L	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30
SMD075L-60V	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30
SMD100L	6.73	7.98	4.80	5.44	0.40	1.00	0.30	0.30
SMD125L	6.73	7.98	4.80	5.44	0.40	0.90	0.30	0.30
SMD150L	6.73	7.98	4.80	5.44	0.40	0.90	0.30	0.30
SMD185L	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30
SMD200L	6.73	7.98	4.80	5.44	0.30	0.90	0.30	0.30
SMD200L-24V	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30
SMD250L	6.73	7.98	4.80	5.44	0.30	0.90	0.30	0.30
SMD260L	6.73	7.98	4.80	5.44	0.30	0.90	0.30	0.30
SMD300L	6.73	7.98	4.80	5.44	0.30	0.90	0.30	0.30
SMD300L-16V	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30
SMD500L	6.73	7.98	4.80	5.44	0.40	1.30	0.30	0.30
SMD500L-13.2V	6.73	7.98	4.80	5.44	0.60	1.30	0.30	0.30

Dimensions & Marking



α = Trademark
300L = Hold current

Recommended Pad Layout (mm)





SMD Series

Alpha-Top (Sea & Land Alliance)


Termination Pad Characteristics

Terminal pad materials : Gold-Plated Nickel-Copper or Tin-plated Nickel-Copper
 Terminal pad solderability : Meets EIA specification RS186-9E and ANSI/J-STD-002 Category 3.


Rework

Use standard industry practices, the removal device must be replaced with a fresh one.

Thermal Derating Curve



Typical Time-To-Trip At 25°C



! WARNING:


- Use PPTC beyond the maximum ratings or improper use may result in device damage and possible electrical arcing and flame.
- PPTC are intended for protection against occasional over current or over temperature fault conditions and should not be used when repeated fault conditions or prolonged trip events are anticipated.
- Device performance can be impacted negatively if devices are handled in a manner inconsistent with recommended electronic, thermal, and mechanical procedures for electronic components.
- Use PPTC with a large inductance in circuit will generate a circuit voltage (L di/dt) above the rated voltage of the PPTC.
- Avoid impact PPTC device its thermal expansion like placed under pressure or installed in limited space.
- Contamination of the PPTC material with certain silicon based oils or some aggressive solvents can adversely impact the performance of the devices. PPTC SMD can be cleaned by standard methods.
- Requests that customers comply with our recommended solder pad layouts and recommended reflow profile. Improper board layouts or reflow profile could negatively impact solderability performance of our devices.



SMD Series

Alpha-Top (Sea & Land Alliance)

Recommended Solder Reflow Conditions




- Recommended reflow methods : IR, vapor phase oven, hot air oven.
 - Devices are not designed to be wave soldered to the bottom side of the board.
 - Recommended maximum paste thickness is 0.25 mm (0.010 inch).
 - Devices can be cleaned using standard method and solvents.
- Note : If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.


Tape And Reel Specifications (mm)

Governing Specifications	EIA 481-2
W	16.0 ± 0.3
P ₀	4.0 ± 0.10
P ₁	8.0 ± 0.10
P ₂	2.0 ± 0.05
A ₀	5.70 ± 0.10
B ₀	8.00 ± 0.10
B _{max.}	12.1
D ₀	1.5 + 0.1, -0
F	7.5 ± 0.05
E ₁	1.75 ± 0.10
E _{min.}	14.25
T _{max.}	0.6
T _{min.}	0.1
K ₀	0.80 ± 0.1
Leader min.	390
Trailer min.	160
Reel Dimensions	
A max.	178
N min.	60
W ₁	16.4 + 2.0, -0.0
W ₂ max.	22.4

EIA Tape Component Dimensions



EIA Reel Dimensions



Storage And Handling

- Storage conditions : 40°C max, 70% R.H.
- Devices may not meet specified performance if storage conditions are exceeded.

Order Information

SMD	050L	Packaging
Product name	Hold	Tape & Reel Quantity 075L-60V 200L-24V 500L-13.2V 1500PCS/reel 2,000 pcs/reel
Size 7555 mm /2920 inch	Current	
SMD : surface mount device	0.50A	

Tape & reel packaging per EIA481-1

Labeling Information

